apollo

Asset integrity and corrosion management of late life assets





Late life assets





Pittodrie Stadium



Stadium 974 Qatar

CoP and Late life






Late life assets are those approaching the cessation of production.



Most late life assets are also ageing assets



Successfully managing late life assets is ensuring that the changes through different life phases are being appropriately and economically managed.



Background





El XXXX Guidelines for Asset Integrity

Management of Offshore Assets Approaching

Cessation of Production to Removal

First edition

Second Draft 5th November 2025





Why Business as Usual Falls



Short

Changing

Priorities

As production winds down, the balance between maintaining maximum output and preparing for decommissioning shifts dramatically. Equipment priorities change.

People &

Knowledge

Retaining skilled personnel becomes difficult amid uncertainty. The loss of experienced engineers represents an irreplaceable loss of institutional knowledge.

External

influences

Shifting regulatory requirements and tax implications can fundamentally alter CoP timelines. Early planning enables operators to capitalize on opportunities and be flexible when needed.

Business as usual assumes stability. Production operations are designed around consistent operational objectives, established procedures, and stable workforce expectations. Late-life operations operate under fundamentally different conditions: shifting business drivers, uncertain timelines, and changing workforce dynamics.

Applying production-phase procedures directly to late-life operations creates misalignment between strategy and execution.

Factors impacting CoP



Asset Condition


- High integrity and repair costs vs. return on investment (ROI).
- Poor condition can accelerate CoP; good condition allows flexibility.

Life Extension Opportunities

- Poor performance or rapid decline may accelerate CoP.
- Potential for new drilling, interventions (e.g., gas lift), or third-party tie-ins.


Single Point Failures (SPFs)

 Risk of failure in critical equipment (e.g., pumps, compressors, export pipelines) that is uneconomical to repair.



External drivers on CoP





- Europe Brent Spot Price FOB



Oil & Gas Price

- Price volatility directly impacts the marginal profitability of late-life assets.
- Commercial & Operator Changes
- Mergers, acquisitions, or asset sale to a different operator
 - Impact of shared infrastructure (e.g., pipelines) or new commercial tie-in opportunities.

Fiscal & Regulatory Environment

- Fiscal: High tax burdens or instability can make an asset non-viable.
- Regulatory: Changing rules, denied license extensions, or new environmental limits.

Late Life Strategies




- Business as usual
- Normal Operations with Ad Hoc Adjustments
 - Operational framework remains unchanged, but individual teams begin making informed judgements about the necessity of certain tasks.
 - Activities such as inspections, maintenance, and fabric maintenance may be selectively deferred, rescheduled, or cancelled based on perceived criticality and remaining service life.
- Formal "Management of Change" (MoC)-Driven Approach
 - Under this model, CoP is treated explicitly as a material change, initiating the company's formal MoC
 process. All scope adjustments, including inspection deferrals and reductions in maintenance activities, are
 formally reviewed and documented through structured MoC protocols.
- Integrated Approach
 - Organisations managing multiple late-life assets commonly adopt an integrated approach. Under this structure, Operations, Plug & Abandonment (P&A), and Decommissioning teams all fall under a pre-defined approach and planning structure. Common planning tools (such as "Decommissioning Passports" or asset integrity handover workshops) ensure aligned strategies across teams and assets.

12 Nov 2025 Late life AIM

Example Timeline




Example Project timeline




Example Integrity timeline

12 Nov 2025



ALARP

- All strategies must ensure the risk to personnel remains As Low As Reasonable Practical (ALARP) throughout
- Generally, reductions in safety are not acceptable
- Duty Holders must maintain necessary competencies,
 - This can be staff or consultants/contractors



Late life integrity framework



Once CoP is declared, the late life strategy is select and the MoC procedure is implemented, the integrity documents should be updated

The inspection planning is normally based on a hierarchy of documents:

Safety Case

Identifying Major Accident Hazards and the approach to controlling the associated risk.

Performance standards

Stating the required performance of all SECEs

Integrity Management Framework

- Integrity strategies
 - Disciple specific definition of how integrity is assured
- Corrosion Risk Assessment Study (CRAS)
 - Determines what corrosion mechanisms are expected to be active in different systems
- Risk Based inspection (RBI)
 - The RBI takes the results of the CRAS and for each system
 - Defines techniques, extent and intervals of inspection
 - After an inspection has been undertaken then the RBI should be updated to reflect the results of the inspection
- Corrosion Management Plans (CMP)
 - Defines the approaches to managing corrosion and environmental cracking, such as chemical treatments, coatings, cathodic protection, process control

CoP ± X years	Operations Activities	Decommissioning Related Activities
-5	Commence CoP / decom review Identify key stages Thorough Review Summary submission	Engage with personnel, contractors, and heavy lift vessel contractors
-5	Develop a management strategy	Develop the Operations to Decommissioning transition plan
	Review & revise RBI / RBA Review & revise FFS data	Develop a critical post CoP systems list
-4	Review inspection data, identify all inspections	Review & revise budgets, plan any extra inspections required to ensure
	Engineering assessments to determine if inspections can be delayed > CoP WSE applies	decommissioning can proceed post CoP
-3	All Integrity inspection activities and anomaly management as per the revised RBI and anomaly management procedures Stop updating RBI's & Intervals after inspection	Planning for P&A, Hydrocarbon free
-2	Defect acceptance criteria are less conservative Inspection reduced, Critical review of temporary repairs Consider early inspection to reduce inspection effort in the last year	
-1	Minimise all inspections and FM	Start system cleaning and shutdown preparation
СоР	Cease HC production Complete EDC Remove HC related performance standards no longer applicable	
CoP + 1	Post CoP inspections to ensure safe for decom & HLV personnel	Complete Decommissioning passport/handover to removal contractor

There is no one-size approach, whilst the operator should have significant control over the operations and hydrocarbon removal phases. The availability of heavy lift vessels may constrain the decommissioning, P&A activities drill rigs, the earlier the operator addresses these the better.

ALARP principle always applies

All relevant Regulations apply

Specific Regulations to be aware of: SCR2015 Reg 23(1), PUWER Reg 7, PUWER Reg 6

12 Nov 2025 Late life AIM

Systems approach



- Each system should be reviewed and the requirements for late life identified
- NORSOK Z-DP-002 is a good source of system list if the current CMMS hierarchy isn't suitable
- The review should involve all stakeholders:
 - Asset management (budget holders)
 - Integrity
 - Operations
 - Decommission



Production Support Utilities system 38 Glycol / methanol regeneration 30 Joi storage 31 Joi storage 32 Loading 33 Joi storage 34	System		Declarati	200	P&A		Hydrocar Warm sta Comments	
33 Oil storage 39 Loading 39 Loading 30 Cooling medium 30 Cooling medium 31 Nooling No	Pro	oduction Support Utilities system	4 - 14 - 15					
Loading	38	Glycol / methanol regeneration	х					
40 Cooling medium 41 Heating medium 42 Chemical injection 43 Depending on reasons for chemical injection possible to reduce from declaration. Equipment with hazardous contents to be to be maintained until EDC complete. 45 Fuel gas 46 Methanol injection 58 Securater and Fresh Water Handling 47 Chlorination 50 Sea water 50 Sea water 51 Ballast water 52 Ballast water 53 Fresh water 54 V X Will be specific to platform requirements/uses 55 Steam 56 Open drain 57 Closed drain 58 V X Sunding structures wont typically have significant life beyond P&A. However, systems to be maintained throughout. 48 Alternative arrangements may be required during cold stack 58 Steam 59 V X Steam 50 Open drain 50 Open drain 51 Closed drain 52 Closed drain 53 Compressed air 54 Oily water 55 Steam 56 Securater 57 Platform Utilities 58 Use of temporary equipment may a simpler solution for some systems 59 Steam 50 Open drain 50 Open drain 51 V X Steam 52 Steam 53 Compressed air 54 Oily water 55 Steam 56 Securater V X Steam 57 Closed drain 58 V X Steam 59 Steam 50 Open drain 50 Open drain 51 V X Steam 51 Det fuel 52 Diesel oil 53 Compressed air 54 Inert gas 55 Steam 57 V X Steam 58 Steam 59 Steam 50 V X Steam 50 Open drain 50 Open drain 51 V X Steam 51 Det fuel 52 Diesel oil 53 Compressed air 54 Inert gas 55 Steam 57 V X Steam 58 Steam 59 Steam 50 Open drain 50 Open drain 50 Open drain 50 Open drain 51 V X Steam 51 Det fuel 52 Diesel oil 53 Compressed air 54 Inert gas 55 Steam 57 V X Steam 58 Steam 59 Steam 50 Open drain 51 V X Steam 51 Det fuel 52 Diesel oil 53 Compressed air 54 Open drain 55 Open drain 56 Open drain 57 Open drain 58 Open drain 59 Open drain 59 Open drain 50 Open drain 51 V X Steam 52 Open drain 53 Open drain 54 Open drain 55 Open drain 56 Open drain 57 Open	33	Oil storage		Х			Last offload, may include slops tanks after cleaning	
Heating medium X Depending on reasons for chemical injection possible to reduce from declaration. Equipment with hazardous contents to be to be maintained until EDC complete. Fuel gas K Methanol injection X Seawater and Fresh Water Handling Tollorination Sea water X Will be specific to platform requirements/uses Ballast water X Floating structures wont typically have significant life beyond P&A. However, systems to be maintained throughout. Sa Fresh water X Alternative arrangements may be required during cold stack Steam X Alternative arrangements may be required for some systems in warm stack Open drain Closed drain X Bunding may be required for some systems in warm stack In the use of temporary equipment may a simpler solution for some systems Solution for some systems Solution for some systems The use of temporary equipment may a simpler solution for some systems Solution for some systems	39	Loading			х		still need for diesel and pot water, until very end	
Depending on reasons for chemical injection possible to reduce from declaration. Equipment with hazardous contents to be to be maintained until EDC complete. 45 Fuel gas 46 Methanol injection Securater and Fresh Water Handling 47 Chlorination 50 Sea water 50 Sea water 51 Ballast water 52 Ballast water 53 Fresh water 54 Alternative arrangements may be required during cold stack 55 Steam 56 Open drain 57 Closed drain 57 Closed drain 58 Closed drain 59 Closed drain 50 Closed originates are colded as a col	40	Cooling medium	х					
possible to reduce from declaration. Equipment with hazardous contents to be to be maintained until EDC complete. 45 Fuel gas	41	Heating medium	X				Ų.	
46 Methanol injection	42	Chemical injection	х				possible to reduce from declaration. Equipment with hazardous contents to be to be maintained until EDC	
Seawater and Fresh Water Handling 47 Chlorination	45	Fuel gas			X			
47 Chlorination	46	Methanol injection	X					
50 Sea water 52 Ballast water 53 Fresh water 54 Steam 55 Steam 56 Open drain 57 Closed drain 58 Closed drain 59 Closed drain 50 Closed drain 51 Jet fuel 52 Diesel oil 53 Compressed air 54 Unert gas 55 Hydraulic power 56 Sewage treatment 57 Will be specific to platform requirements/uses 58 K Floating structures wont typically have significant life beyond P&A. However, systems to be maintained throughout. 5 Alternative arrangements may be required during cold stack 5 Bunding may be required for some systems in warm 5 Stack 5 Bunding may be required for some systems in warm 5 Stack 5 The use of temporary equipment may a simpler 5 Solution for some systems 5 Solution for some systems	Se	awater and Fresh Water Handlin	g	400	711	1111	A CONTRACTOR OF THE CONTRACTOR	
52 Ballast water x Floating structures wont typically have significant life beyond P&A. However, systems to be maintained throughout. 53 Fresh water x Alternative arrangements may be required during cold stack 55 Steam x Alternative arrangements may be required during cold stack 56 Open drain x Bunding may be required for some systems in warm stack 40 Oily water Platform Utilities 61 Jet fuel x The use of temporary equipment may a simpler solution for some systems x Solution for some systems 63 Compressed air x A Solution for some systems 64 Inert gas 65 Hydraulic power x X Solution for some systems	47	Chlorination			Х			
beyond P&A. However, systems to be maintained throughout. 53 Fresh water	50	Sea water		Х			Will be specific to platform requirements/uses	
cold stack Cold stack Cold stack Cold stack	52	Ballast water				х	beyond P&A. However, systems to be maintained	
Drainage 56 Open drain 57 Closed drain 58 Sewage treatment X Bunding may be required for some systems in warm stack X Stack Bunding may be required for some systems in warm stack X Stack The use of temporary equipment may a simpler solution for some systems X Solution for some systems	53	Fresh water			х			
56 Open drain	55	Steam	х					
56 Open drain								
57 Closed drain	Dr	ainage		-11-	-	li i	ie.	
44 Oily water x x Platform Utilities 61 Jet fuel x The use of temporary equipment may a simpler 62 Diesel oil x solution for some systems 63 Compressed air x x 64 Inert gas x x 65 Hydraulic power x x x 66 Sewage treatment x x	56	Open drain			X		Bunding may be required for some systems in warm	
Platform Utilities 61 Jet fuel	57	Closed drain		Х			stack	
61 Jet fuel x The use of temporary equipment may a simpler 62 Diesel oil x solution for some systems 63 Compressed air x 64 Inert gas x 65 Hydraulic power x 66 Sewage treatment x	44	Oily water		Х				
62 Diesel oil	Pk	atform Utilities						
63 Compressed air x 64 Inert gas x 65 Hydraulic power x 66 Sewage treatment x	61	Jet fuel			x		The use of temporary equipment may a simpler	
64 Inert gas x 55 Hydraulic power x 56 Sewage treatment x 56 Hydraulic power 57 K 58 Hydraulic power 58 Hydr	62	Diesel oil			х		solution for some systems	
65 Hydraulic power x 66 Sewage treatment x	63	Compressed air			х			
66 Sewage treatment x	64	Inert gas		Х				
	65	Hydraulic power	х					
69 Lubrication oil x	66	Sewage treatment			х			
	69	Lubrication oil			х			

Deluge and hazardous zones



- The Zone approach influences the CRAS and RBI insofar that it affects the Consequences of Failure (CoF) and Risk of Failure (RoF)
- If the Zone classification of an area / module is reduced, it can decrease the CoF and RoF calculations
- Most areas will have multiple systems, all of which must me made hydrocarbon free to allow re-classification
- Re-zoning involves considerable work to justify the changes, is likely to affect the Safety Case and will require Regulatory approvals. Typically, this is not done until the platform is declared hydrocarbon free.
- Realistically re-zoning does not affect inspections of process equipment but is more significant with regards to safety systems.
- There is only value in re-zoning if there is a very significant justification, typically if a complete train or module is mothballed or made redundant, then the safety systems can be reduced.
- It may be prudent to use temporary deluge systems in some instances; these will require little to no inspection and can be installed relatively quickly



Inspection effectiveness




- Inspection effectiveness refers to how well an inspection method detects deterioration mechanisms
- It can be used to adjust the Probability of Failure (PoF) in Risk-Based Inspection.
- Examples of reduction in efficiency in late life may include:
 - Reduction in volume of inspection
 - Extent of UT
 - ☐ Only at bottom of pipe, or know problem areas
 - Substitution of Techniques
 - Nonintrusive inspection of vessels (HOIS guidelines)
 - UT instead of RAD
 - Visual weld inspection instead of Penetration
 - Use of drones for close visual inspection
 - Fix on fail methods
- Guidance on effectiveness can be found in API 581 and similar codes

LEVEL	Meaning	Impact on Probability io Failure
Α	High probability of detecting damage	PoF decreases significantly
В	Reasonable detection capability	Moderate decrease in PoF
С	Basic inspection with limited detection	Small decrease in PoF
D	Minimal detection capability	PoF nearly unchanged
E	No meaningful inspection	PoF remains high

RBI Inspection frequency	Inspection date (years before COP)	Inspection Effectiveness Reduction One level		
5	5			
4		No change		
3		No change		
2		No change		
4	4	Two levels		
3		One level		
2		No change		
3	3	Two levels		
2		One level		
2	2	Two levels		

Inspection techniques







Structures



- Generally, structures will be required to have sufficient integrity until the removal is complete
- Therefore, some integrity management will be ongoing
- For jackets it may not be practicable to install full subsea repairs in last years of life
- Partial repairs may be acceptable or more advanced assessments
- Operation controls can be used to mitigate risk such as setting adverse weather limits to down-man the platform






Displacement x10

Structures – defined life repairs





Scaffold boards covering degraded deck plate



Scaffold supporting degraded structures

Preparation for decom

- Preparation for removal does not fall under the integrity team
- However, specific equipment may be required until removal is complete
 - Cranes
 - Utilities, power and water
 - Access structures
 - Caissons
 - Lift points
- Often more efficient to perform activities with core crew than a separate team
- RBI and planning should account for sontinued monitoring of a puired systems post CoP



Next steps



- What significant operational transitions are on your horizon?
 - Early engagement will position your organisation to make strategic choices rather than reactive responses.
 - What elements of the proactive approach can you implement immediately in your organisation?
- Are you engaging in the necessary collaboration?
 - Successful late-life management requires alignment across operations, decommissioning, finance, and leadership.
 - Do you have the information needed to implement systematic late-life strategies?
- Look out for the Energy Institute's upcoming guidance, available through the website

Questions?





12 Nov 2025

apollo

Engineering tomorrow, today.







