



P&A Success with New Technologies Designed for Annulus Remediation in Challenging Subsea HPHT Well

Presenters:

Jason Bassi, Shell (UK) Ltd.

Dayln Beazer, PEng, Lee Energy Systems



Cautionary Note

•The companies in which Royal Dutch Shell plc directly and indirectly owns investments are separate legal entities. In this presentation “Shell”, “Shell group” and “Royal Dutch Shell” are sometimes used for convenience where references are made to Royal Dutch Shell plc and its subsidiaries in general. Likewise, the words “we”, “us” and “our” are also used to refer to Royal Dutch Shell plc and subsidiaries in general or to those who work for them. These terms are also used where no useful purpose is served by identifying the particular entity or entities. “Subsidiaries”, “Shell subsidiaries” and “Shell companies” as used in this presentation refer to entities over which Royal Dutch Shell plc either directly or indirectly has control. Entities and unincorporated arrangements over which Shell has joint control are generally referred to as “joint ventures” and “joint operations”, respectively. Entities over which Shell has significant influence but neither control nor joint control are referred to as “associates”. The term “Shell interest” is used for convenience to indicate the direct and/or indirect ownership interest held by Shell in an entity or unincorporated joint arrangement, after exclusion of all third-party interest.

•This presentation contains forward-looking statements (within the meaning of the U.S. Private Securities Litigation Reform Act of 1995) concerning the financial condition, results of operations and businesses of Royal Dutch Shell. All statements other than statements of historical fact are, or may be deemed to be, forward-looking statements. Forward-looking statements are statements of future expectations that are based on management’s current expectations and assumptions and involve known and unknown risks and uncertainties that could cause actual results, performance or events to differ materially from those expressed or implied in these statements. Forward-looking statements include, among other things, statements concerning the potential exposure of Royal Dutch Shell to market risks and statements expressing management’s expectations, beliefs, estimates, forecasts, projections and assumptions. These forward-looking statements are identified by their use of terms and phrases such as “aim”, “ambition”, “anticipate”, “believe”, “could”, “estimate”, “expect”, “goals”, “intend”, “may”, “objectives”, “outlook”, “plan”, “probably”, “project”, “risks”, “schedule”, “seek”, “should”, “target”, “will” and similar terms and phrases. There are a number of factors that could affect the future operations of Royal Dutch Shell and could cause those results to differ materially from those expressed in the forward-looking statements included in this [report], including (without limitation): (a) price fluctuations in crude oil and natural gas; (b) changes in demand for Shell’s products; (c) currency fluctuations; (d) drilling and production results; (e) reserves estimates; (f) loss of market share and industry competition; (g) environmental and physical risks; (h) risks associated with the identification of suitable potential acquisition properties and targets, and successful negotiation and completion of such transactions; (i) the risk of doing business in developing countries and countries subject to international sanctions; (j) legislative, fiscal and regulatory developments including regulatory measures addressing climate change; (k) economic and financial market conditions in various countries and regions; (l) political risks, including the risks of expropriation and renegotiation of the terms of contracts with governmental entities, delays or advancements in the approval of projects and delays in the reimbursement for shared costs; and (m) changes in trading conditions. No assurance is provided that future dividend payments will match or exceed previous dividend payments. All forward-looking statements contained in this [report] are expressly qualified in their entirety by the cautionary statements contained or referred to in this section. Readers should not place undue reliance on forward-looking statements. Additional risk factors that may affect future results are contained in Royal Dutch Shell’s 20-F for the year ended December 31, 2018 (available at www.shell.com/investor and www.sec.gov). These risk factors also expressly qualify all forward looking statements contained in this presentation and should be considered by the reader. Each forward-looking statement speaks only as of the date of this presentation, May 30, 2019. Neither Royal Dutch Shell plc nor any of its subsidiaries undertake any obligation to publicly update or revise any forward-looking statement as a result of new information, future events or other information. In light of these risks, results could differ materially from those stated, implied or inferred from the forward-looking statements contained in this presentation.

•We may have used certain terms, such as resources, in this presentation that United States Securities and Exchange Commission (SEC) strictly prohibits us from including in our filings with the SEC. U.S. Investors are urged to consider closely the disclosure in our Form 20-F, File No 1-32575, available on the SEC website www.sec.gov.

•

Well History – Pre 2018 P&A


- HPHT Appraisal Well (vertical) drilled in 1985 and suspended.
- Returned to well in 2015 > unable to complete abandonment due to live 7" annulus

Well Status Pre 2018 P&A:


- Suspended with kill string on DLT packer
- 15.4ppg Oil Based Mud
- 7" casing had flush connections (FL-4S)

Reservoir Data:

- Fulmar reservoir pressure of 13,000psi & 332degF



Abandonment Isolation Strategy



Environmental Barrier

- Perforate, Circulate, Cement for 9 5/8 x 13 3/8" x 20"

Intermediate Horda Abandonment barrier

- 9000ft
- Set inside 9 5/8" casing
- Squeezing shale or PWC

7" Annulus Deep Barrier

- 12,500ft
- Set inside 7" casing (flush joint)


Technology Review

Challenge:

- Must perforate or cut 7" – 38# P110 flush joint casing under HPHT conditions
- Maintaining the integrity of the 9-5/8" intermediate string.

Solution:


- Hydro-mechanical casing cutter (Lee Gator Perforator) was selected.



Technology Review

Hydro-Mechanical Casing Cutter:

- Provide access to the B-Annulus without the risk of compromising the intermediate casing string.
- Allows for full and effective clean of A-Annulus.
- Centralization of the 7" casing if laying on the low side.



Technology Redesign

Challenge:

- No tool that would fit in the current casing size under the extreme HPHT.
- A Heavy Wall Gator System was designed for this particular well.
- The new tool was designed with the following parameters:
 - HPHT well conditions
 - Heavy wall perforating performance >> Able to cut casing and produce 2.7 X more output force.
 - New materials were selected and a custom tool was built.

Gator Tool		570 HD	570 HD	570 HWG	570 HWG + re-hardened blades
Test		1	2	3	4
Date		August 2017	Oct 2017	Jan 2018	June 2019
Pistons		12	12 + 4 thick walled – all high grade	14 + 4 thick walled – all high grade	14 + 4 thick walled – all high grade
Tool Body/Blade Material Upgrades		Standard grade steel	Pistons upgraded to higher grade steel	Pistons/tool body higher grade steel Blade/travel block machined as one part	Pistons/tool body higher grade steel Blades -re-treated the for a hardness of 55-58 HRC (originally 52HRC).
Max Allowable Pressure (psi)		3300	3600 (4000)	4500 (5000)	4500 (5000)
Max tool output force (lbs)		440,000lbs	780,000lbs	1,200,000lbs	1,200,000lbs
Testing	7" 38# P110	14cuts made - failure of pistons closest to tool	10 cuts made successfully	18 cuts made successfully – Blades wore out prematurely	50 cuts made successfully
	7" eccentric inside 9 5/8"		Barite filled annulus – 5cuts Barite/5% cement – 1 partial cut, 2 nd cut tool body/blade failure at 3590psi	Cement filled annulus - successful limit test of tool taken to limit of 4500psi, no breach of 7" casing	


Technology Testing & Verification

Shop Testing in Canada and UK:

- Gator Testing and Tool Validation carried out in Canada .
 - Tool function tested
 - Test targets cut
 - Multiple cycles for tool validation
- HydraHemera Testing and Tool Validation carried out in Norway .
 - Three test fixtures manufactured for casing cut at 1ft, 2ft, & 3ft spacings.
 - The annulus was then filled with a barite, sand and cement mix and left to cure.
 - Nozzle angles re-configured to achieve optimum flow and cleaning of annulus through Gator casing cuts.

3.3 2 ft. spacing flow test

The annulus was successfully cleaned except for two small remnants of annulus fill ($\pm 95\%$ clean).



3.4 1 ft. spacing flow test

The annulus fill was successfully cleaned out across the entire perforated interval (100% clean).




Stabiliser

HydraHemera

Cementing tool

Jet-wash tool


Base for cement



Results & Summary

Abandonment Summary:

- Challenging Deep 7" Annulus Barrier set successfully and inflow tested – enabled with Gator tool and use of HydraHemera™ PWC® system for cement placement .
 - Lost ~ 2500bbls of due to losses event.
 - 4 cement squeezes performed to create base for PWC operations.
 - Total of 146 Gator Perforations performed, world 1st centralising casing to enable annulus remediation with HydraWell HydraHemera™ system.
- Total of 500bbls cement pumped, 4 cement squeeze jobs , with 1 PWC cement job (71bbls) providing the deep well control barrier to enable full abandonment.



Questions

